

IP-SEA-008C3POM16	19"/2U Managed Rack kWh PDU, per outlet kWh metering, 3.6kW, outlets (8)C13, input C20 (1x16A), without input cord
-------------------	--

# 037292DIB11- IPSEA008C3POM16

MANAGED PDU

IP-SEA-008C3POM16

## SPECIFICATIONS

DIMENSIONS	L x W x D = 440 x 65 x 105 mm (1.5 U) (excl. strain relief, mounting & cable bending radius)
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)
MOUNT	sidecover 19 inch double deep housing
POWER INPUT	single phase 16 A, 230VAC - 50/60Hz
CABLE ENTRY	power entry rear-side left
CABLE & PLUG	C20 16A chassis
CONNECTIVITY	databus: 2 x RJ45   Ethernet: RJ45   sensorport: RJ11   USB
INPUT METERING	volt, ampere, kWh, power factor
SWITCHED OUTLETS	8 times bistable close to zero crossing switching relays
METERED OUTLETS	8 times volt, ampere, kWh, power factor
FUSES	n/a
DISPLAY	LCD display with backlight and configurable orientation
OUTLETS	8 x IEC 60320 C13

### Summary

- double horizontal PDU
- single phase 16 A
- metered input
- metered outlets, switched outlets
- 8 outlets

