

IP-SEA-318C36C932

*Enhanced Managed Rack kWh PDU, 0U,
7.2kW, outlets (18)C13 and (6)C19, input plug EN 60309 (1x32A), cord 3m*

Vertical PDU (0 U), single phase 32 A, input metering, output switching (18 x C13) (6 x C19)

24 outlet PDU
Vertical mounting (0U)
single phase
32 amps
1.700 mm aluminum profile. Length without strain relief and mounting brackets
power entry front-side top
Power lead (3G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)
input metered 1 phase w/ display, databus, ethernet and sensor port

sidecover flat
thermal breaker 16A (ETA)
module for 9 fold individual outlet switching
2 x C13 10A chassis outlet (triple)
C13 10A chassis outlet
2 x C19 16A outlet
thermal breaker 16A (ETA)
module for 9 fold individual outlet switching
2 x C13 10A chassis outlet (triple)
C13 10A chassis outlet
2 x C19 16A outlet
thermal breaker 16A (ETA)
module for 9 fold individual outlet switching
2 x C13 10A chassis outlet (dual)
2 x C19 16A outlet
sidecover flat

Toolless mount brackets
Toolless mount brackets

Optional accessory:
Digital humidity/ temperature sensor with 2.5 meter cable

