

**IP-SEA-318C36C9PBM32**

Managed Rack kWh PDU, 0U, input and per branch kWh metering, 7.2kW, outlets (18)C13 and (6)C19, input plug EN 60309 (1x32A), power cord 3m

## 95E9VMS1322- IPSEA318C369BM3

SWITCHED PDU


IP-SEA-318C36C9PBM32

### SPECIFICATIONS

**DIMENSIONS** L x W x D = 1375 x 65 x 52.5 mm (0U)  
(excl. strain relief, mounting & cable bending radius)

**ENCLOSURE** Profile color black, aluminium with stainless steel covers (IP20)

**MOUNT** Toolless mount buttons (brackets not included)  
(distance=800, positions=287.4, 1087.6mm)



**POWER INPUT** single phase 32 A, 230VAC - 50/60Hz

**CABLE ENTRY** power entry front-side top

**CABLE & PLUG** Power lead (3G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)



**CONNECTIVITY** databus: 2 x RJ45 | Ethernet: RJ45 | sensorport: RJ12 | USB

**BRANCH METERING** 2 x volt, ampere, kWh, power factor

**SWITCHED OUTLETS** 24 times bistable close to zero crossing switching relays

**FUSES** 2 x Thermal breaker 16A (ETA)

**DISPLAY** LCD display with backlight and configurable orientation

**OUTLETS** 18 x IEC 60320 C13 , 6 x IEC 60320 C19

### 4. Summary

- vertical PDU (0 U)
- single phase 32 A
- metered branches (2x)
- switched outlets
- 24 outlets