

IP-SEI-3-INLINE16	Inline meter 3.6kW, single phase 16A, input metering, pass through (1 x Cable); length 280mm; input cable 3m, output cable 0.5m, plug & outlet EN60309; black case
-------------------	--



040477VIP11- IPSEI3INLINE16

INLINE METER

SPECIFICATIONS

DIMENSIONS	L x W x D = 280 x 65 x 52.5 mm (0U) (excl. strain relief, mounting & cable bending radius)
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)
MOUNT	sidecover table mount
POWER INPUT	single phase 16 A, 230VAC - 50/60Hz
CABLE ENTRY	power entry side-cover top
CABLE & PLUG	Power lead (3G2,5 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)
CONNECTIVITY	dabus: 2 x RJ45 Ethernet: RJ45 sensorport: RJ11 USB
INPUT METERING	volt, ampere, kWh, power factor
FUSES	n/a
DISPLAY	LCD display with backlight and configurable orientation
OUTLETS	1 x Exit lead (3G2,5 halogenfree) with IEC60309 socket 0,5m

Summary

- vertical PDU (0 U)
- single phase 16 A
- metered input
- inline
- 1 outlets



IP-SEI-3-INLINE16-RD	Inline meter 3.6kW, single phase 16A, input metering, pass through (1 x Cable); length 280mm; input cable 3m, output cable 0.5m, plug & outlet EN60309; red case
----------------------	--



040481VIP11- IPSEI3INLINE16R

INLINE METER

SPECIFICATIONS

DIMENSIONS	L x W x D = 280 x 65 x 52.5 mm (0U) (excl. strain relief, mounting & cable bending radius)
ENCLOSURE	Profile color red, aluminium with stainless steel covers (IP20)
MOUNT	sidecover table mount
POWER INPUT	single phase 16 A, 230VAC - 50/60Hz
CABLE ENTRY	power entry side-cover top
CABLE & PLUG	Power lead (3G2,5 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)
CONNECTIVITY	databus: 2 x RJ45 Ethernet: RJ45 sensorport: RJ11 USB
INPUT METERING	volt, ampere, kWh, power factor
FUSES	n/a
DISPLAY	LCD display with backlight and configurable orientation
OUTLETS	1 x Exit lead (3G2,5 halogenfree) with IEC60309 socket 0,5m

Summary

- vertical PDU (0 U)
- single phase 16 A
- metered input
- inline
- 1 outlets



