

**IP-SEI-336C36C922**

Enhanced Monitored Rack kWh PDU, 0U, 22kW, outlets (36)C13 and (6)C19, input plug EN 60309 (3x32A), cord 3m



## IP-SEI-336C36C922

### METERED PDU

### SPECIFICATIONS

#### 6. Summary

- vertical PDU (0 U)
- three phase 32 A
- metered input
- 42 outlets

**DIMENSIONS** L x W x D = 1325 x 65 x 52.5 mm (0U)  
(excl. strain relief, mounting & cable bending radius)

**ENCLOSURE** Profile color black, aluminium with stainless steel covers (IP20)

**MOUNT** Toolless mount buttons (brackets not included)  
(distance=800, positions=262.4, 1062.6mm)



**POWER INPUT** three phase 32 A, 230/400V - 50/60Hz

**CABLE ENTRY** power entry front-side top

**CABLE & PLUG** Power lead (5G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)



**CONNECTIVITY** databus: 2 x RJ45 | Ethernet: RJ45 | sensorport: RJ12 | USB

**INPUT METERING** volt, ampere, kWh, power factor

**FUSES** 6 x Thermal breaker 16A (ETA)

**DISPLAY** LCD display with backlight and configurable orientation

**OUTLETS** 36 x IEC 60320 C13 , 6 x IEC 60320 C19