

IP-SEI-336C36C932

Monitored Rack kWh PDU, 0U, input and per branch kWh metering, 7.2kW, outlets (36)C13 and (6)C19, input plug EN 60309 (1x32A), power cord 3m



IP-SEI-336C36C932

BRANCH METERED PDU

SPECIFICATIONS


DISPLAY LCD display with backlight and configurable orientation

CONNECTIVITY databus: 2 x RJ45 | Ethernet: RJ45 | sensorport: RJ12 | USB

ENCLOSURE Profile color black, aluminium with stainless steel covers (IP20)

DIMENSIONS L x W x D = 1160 x 65 x 52.5 mm (0U)
(excl. strain relief, mounting & cable bending radius)

MOUNT Toolless mount buttons (brackets not included)
(distance=800, positions=180.0, 980.0mm)



POWER INPUT single phase 32 A, 230VAC - 50/60Hz

CABLE ENTRY power entry front-side top

CABLE & PLUG Power lead (3G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)



BRANCH METERING 2 x volt, ampere, kWh, power factor

OUTLETS 36 x IEC 60320 C13 , 6 x IEC 60320 C19

FUSES 2 x Thermal breaker 16A (ETA)

2. Summary

- vertical PDU (0 U)
- single phase 32 A
- metered inputs
- metered branches (2x)
- 42 outlets