


IP-SEI-336C36C9POM11

Monitored Rack kWh PDU, 0U, per outlet kWh metering, 11kW, outlets (36)C13 and (6)C19, input plug EN 60309 (3x16A), cord 3m



037289VIM31- IPSEI336C36OM11

MONITORED PDU

IP-SEI-336C36C9POM11

SPECIFICATIONS

DIMENSIONS	L x W x D = 1735 x 65 x 52.5 mm (0U) (excl. strain relief, mounting & cable bending radius)
ENCLOSURE	Profile color black, aluminium with stainless steel covers (IP20)
MOUNT	Toolless mount buttons (brackets not included) (distance=1422, positions=156, 1578mm)
POWER INPUT	three phase 16 A, 230/400V - 50/60Hz
CABLE ENTRY	power entry front-side top
CABLE & PLUG	Power lead (5G2,5 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)
CONNECTIVITY	databus: 2 x RJ45 Ethernet: RJ45 sensorport: RJ11 USB
INPUT METERING	volt, ampere, kWh, power factor
METERED OUTLETS	42 times volt, ampere, kWh, power factor
FUSES	n/a
DISPLAY	LCD display with backlight and configurable orientation
OUTLETS	36 x IEC 60320 C13 , 6 x IEC 60320 C19

Summary

- vertical PDU (0 U)
- three phase 16 A
- metered input
- metered outlets
- 42 outlets

