

**IP-SEA-318C36C922**

*Enhanced Managed Rack kWh PDU, 0U, 22kW, outlets (18)C13 and (6)C19, input plug EN 60309 (3x32A), power cord 3m*

Vertical PDU (0 U), three phase 32 A, input metering, output switching (18 x C13) (6 x C19)

24 outlet PDU  
Vertical mounting (0U)  
3 phase  
32 amps  
1.700 mm aluminum profile. Length without strain relief and mounting brackets  
power entry front-side top  
Power lead (5G6 halogenfree) with CEE plug 3,0m (strain relief height 2,5cm)  
input metered 3 phase w/ display, databus, ethernet and sensor port

sidecover flat

**module for 9 fold individual outlet switching**

thermal breaker 16A (ETA) phase 1

3 x C13 10A chassis outlet (dual, square)

thermal breaker 16A (ETA) phase 2

C13 10A chassis outlet (triple)

**module for 9 fold individual outlet switching**

phase 2

C13 10A chassis outlet (triple)

thermal breaker 16A (ETA) phase 3

3 x C13 10A chassis outlet (dual, square)

**module for 9 fold individual outlet switching**

thermal breaker 16A (ETA) phase 1

2 x C19 16A outlet

thermal breaker 16A (ETA) phase 2

2 x C19 16A outlet

thermal breaker 16A (ETA) phase 3

2 x C19 16A outlet

sidecover flat

Toolless mount brackets

Toolless mount brackets

Optional accessory:

Digital humidity/ temperature sensor with 2.5 meter cable

